



APPLICATIONS

- Gases
- Liquids

TECHNICAL SPECIFICATIONS

Temperature Range °C	max +1083
Material	CU
Material according to	ASTM B68 DIN 1787
Tolerances according to	ASTM B251 DIN 1754
Color	black
Burst Pressure	1.5 x operating pressure

PRODUCT INFORMATION

Copper pipe (soft, on coil)	P	D	d	s	MOQ	Kg/ 1 m
4 x 2	180	4.00	2.00	1.00	On request	0.1
6 x 4	140	6.00	4.00	1.00	On request	0.14
8 x 6	100	8.00	6.00	1.00	On request	0.2
10 x 8	80	10.00	8.00	1.00	On request	0.25
12 x 10	65	12.00	10.00	1.00	On request	0.31
14 x 12	33	14.00	12.00	1.00	On request	0.37
15 x 13	30	15.00	13.00	1.00	On request	0.39

1/4" od	100	6.35	4.83	0.76	On request	0.119
3/8" od	65	9.52	7.92	0.80	On request	0.198
1/2" od	40	12.7	10.90	0.90	On request	0.27

Bar = operating pressure at 23 °C

Copper pipe (on length)	P	D	d	s	MOQ	Kg/ 1 m
6 x 4	200	6.00	4.00	1.00	On request	0.14
8 x 6	135	8.00	6.00	1.00	On request	0.2
10 x 8	100	10.00	8.00	1.00	On request	0.25
12 x 10	81	12.00	10.00	1.00	On request	0.31
14 x 12	73	14.00	12.00	1.00	On request	0.37
15 x 13	66	15.00	13.00	1.00	On request	0.39
18 x 15	60	18.00	15.00	1.50	On request	0.7
22 x 19	41	22.00	19.00	1.50	On request	0.87
28 x 25	30	28.00	25.00	1.50	On request	0.12

Bar = operating pressure at 23 °C

- MOQ = Minimum order quantity
- P = pressure (bar)
- D = tube outside diameter (mm)
- d = tube inside diameter (mm)
- s = wall thickness (mm)

